



F-150 CONSTRUCTION HEATER/CHAUFFAGE DE CONSTRUCTION

SPECIFICATIONS:	
Model	F-150
Fuel	Vapor propane
Input (maximum)	150,000 btuh
(minimum)	50,000 btuh
Manifold pressure	2½ to 20 psig
Hose length	20-ft standard
Regulator with POL	Preset at 20 psig max
Approved	ULC listed
Weight	27 lbs
Dimensions	30" x 11¼" x 14"
Air Outlet	8" diameter
Fuel Consumption	2.3 – 6.9 lbs per hour
Ignition	Manual

SPECIFICATIONS :	
Modèle	F-150
Combustible	Propane de vapeur
Contribution (maximum)	150,000 btuh
(minimum)	50,000 btuh
Pression multiple	2½ à 20 psig
Longueur de tuyau	20 pd norme
Régulateur avec POL	Programmé à 20 psig max
Approuvé	ULC Énuméré
Poids	27 livres
Dimensions	30" x 11¼" x 14"
Issue aérienne	8" diamètre
Consommation du Combustible	2.3 à 6.9 livres par heure
Ignition	Manuel

Clearance to combustibles:			Déblayage aux combustibles :		
ABOVE	IN FRONT	SIDE	EN HAUT	EN AVANT	A COTE
5-feet	8-feet	2-feet	5-pied	8-pied	2-pied