



ST35

Track Loaders



ST 35 Radial Lift Track Loader

The ST 35 radial lift track loader delivers power and maneuverability. This machine delivers 3,500 pounds of rated operating capacity at 50% and a lift height up to 125 inches. The ST 35 is powered by a 74.3 hp turbo-charged Perkins Tier IV Final engine. Available in both H-Patter and ISO joystick pilot controls, the machines can fit the preferences of any user. The ergonomically designed controls and pressurized cab delivers comfort and visibility, reducing operator fatigue and increasing productivity.

- Standard two-speed transmission increases travel time on job sites giving the operator more time throughout the day to get more tasks completed.
- Spacious extended cab maximizes room and comfort for the operator to move inside the cab.
- Quick and easy service access from the forward tilting cab and the arrangement of internal components makes it easy to maintain the machine.
- Hydraulically driven fan operates on an as-needed basis allowing faster warm-up times of the engine and significantly reducing noise.
- Optional high flow hydraulics increase the range of usable attachments improving efficiency and productivity.

Technical specifications



ST 35

Operating data

Height Top Of Rops	82 in
Overall length w/ bucket	144 in
Overall length w/o bucket	116 in
Height Hinge Pin Max	125 in
Operating weight	9,827 lb
Rated Operating Capacity ROC 50%	3,500 lb
Rated Operating Capacity ROC 35%	2,425 lb
Length of track on ground	63 in
Dumping height at max height	95.2 in
Tipping angle (Bucket dump) w/ bucket at max height	45 °
Ground clearance	9.5 in
Bucket width	80 in
Width w/o bucket	78 in
Width Track	17.7 in

Engine / Motor

Engine / Motor	Turbo-Charged Perkins 854 Tier 4 Final
Engine performance	74.3 hp
Tank capacity Fuel	24.3 US gal

Hydraulic system

Auxiliary Hydraulics- Standard Flow	22.5 US gpm
Auxiliary Hydraulics- High Flow	36 US gpm
Pressure Aux. relief	3,338 psi

Power transmission

Travel speed Low	4.3 mph
Travel speed High	8.7 mph



**WACKER
NEUSON**
all it takes!

Dimensions

Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions.

Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2016 Wacker Neuson SE.