

# 1404 Track Excavator, with Canopy and Long Dipperstick

Item Number: 0620490

# 1404

## High performance on any job site

>> A compact excavator in the 1.5-ton class, this unit is ideally suited for excavating applications in tight spaces. The 1404 features a canopy compliant with FOPS, TOPS and ROPS regulations. Two models are available, a short and long dipperstick. Powered by the economical Yanmar 3-cylinder diesel engine, the 1404 track excavator offers rubber track, dozer blade and boom-mounted working light. Hydraulic system features load sensing system, hydraulic oil cooler, hydraulic pilot control via joystick, dipperstick-mounted auxiliary hydraulic connection for two directions of motion and control pattern change system. View Complete Brochure <<



## Additional Advantages

- A telescopic undercarriage can be extended from 39" to 52" for greater lifting power and stability.
- Largest operator station in its class for easy access and operator comfort.
- Load sensing system offers easy and precise control.
- Positioning of boom cylinder on top of the boom offers greater boom and hose protection.
- The large engine cover and easy removal of side covers provide for easy access and excellent serviceability.
- Unit equipped with pattern control selector valve for versatility and ease of use.

Description	Metric	Imperial
Engine Make	Yanmar	
Model	3TNV76	
Engine Type	Water cooled 3- cylinder diesel engine	
Max. power output according to DIN-ISO 3046*	17,9 kW	24.3 hp
Fuel tank capacity	24 l	6.34 US gal
Speed	2,5 km/h	1.5 mph
Shipping weight	1.515 kg	3,340 lb
Max. digging depth	2,24 m	7.33 ft
Max. dump height	2,37 m	7.75 ft
Max. reach (on the ground)	3,65 m	11.91 ft
Max. swing angle to the right/left	43/73 °	43/73 °
Max. arm force	724 kg	1,596 lb
Max. bucket force	1.448 kg	3,192 lb
Height of canopy / cab	2,27 m	7.5 ft
Width	In-0,99 / Out-1,30 m	In-3.25 / Out-4.33 ft
Transport length (boom down)	3,64 m	12 ft
Length, dipper stick	1,1 m	3.7 ft
Pump	1-gear pump	
Hydraulic pump flow	34,5 l/min	9 US gpm
Operating pressure working / driving hydraulics	200 bar	2,901 psi
Operating pressure swing gear	150 bar	2,176 psi
Hydraulic tank capacity	20 l	5 US gal
Blade width	0,99 m	3.2 ft
Blade height	232 mm	9 in
Blade max. lift above ground	211 mm	8 in
Blade max. lift below ground	264 mm	10 in
Width track-in / track-out	0,99/1,30	

### Standard Package - 1404

includes operator's manual and parts list.

Please refer to our Price List and Ordering Guide for complete accessory information.

Specifications may change due to continuous product development. Users are advised to consult Wacker Neuson's Operator's Manual and website for specific information regarding the engine power rating. Actual power output may vary due to conditions of specific use.

Generated on Monday, August 13, 2012

