

WL 30 Professional Wheel Loader, 3.0t

Item Number: 0620588

WL 30

This wheel loader is dependable, durable and environmentally friendly.

>> The Wacker Neuson WL 30 wheel loader delivers extremely high performance. Even under continuous use, ample operator comforts reduce fatigue and increase productivity. This rugged unit offers unmatched performance while protecting the environment with low emissions. The workhorse of the construction site, the durable WL 30 features better break-out force, digging and lifting capabilities along with high dump heights. <<



Additional Advantages

- Efficient operation where engine efficiency reduces operating costs
- Higher payloads provide better break-out force and lifting capacity
- Ergonomic design with operator comforts that improve productivity
- Higher resale value as compared to alternative skid steer loaders
- Operating elements arranged ergonomically next to the driver's seat; multi-functional singlelever control; additional lever for 3rd control circuit
- Vibration-dampened ROPS (Roll Over Protection System) and FOPS (Falling Object Protection System) located on the rear frame. (Some models feature fully enclosed cab.)
- Excellent visibility; infinitely adjustable steering column; platform is side tilting for better serviceability
- PZ-combination lift frame and universal coupler system
- Hydraulically operated centrally-articulated pendulum steering

Description	Metric	Imperial
Engine Type	Perkins (404 C - 22), 4-cylinder	
Engine Power (at 2800 rpm)*	35.7 kW	48 hp
Speed	0 - 20 km/h	0 - 12.43 mph
Bucket capacity	0.45 m ³	0.59 yd ³
Drive	Hydrostatic all-wheel drive with steering wheel	
Axles	Outboard planetary axles	
Differential lock	100% electric-hydraulic switchable front and rear axle	
Brakes	Hydrostatic drive and hub brake with braking-inching pedal, operating on all 4 wheels	
Standard tires	31 x 15.5 - 15 EM (Earth moving tires)	
Overall length	4554 mm	179.3 in
Max. height of bucket pivot	3209 mm	126 in
Max. dump height	2416 mm	95 in
Height of cab	2251 mm	88.6 in
Inside turning radius	1431 mm	55.6 in
Outside turning radius	2793 mm	110 in
Operating weight	3120 kg	6978.5 lb
Total width, standard	1345 mm	53 in
Hydraulic pump flow	49 lpm	12.9 gpm
System pressure	210 bar	3045 psi
Hydraulic lifting capacity	3292.7 kg	7259.1 lb
Breake-out force	4043 kg	9089 lb
Tipping load with bucket	2013 kg	4437.9 lb
Tipping loads with bucket (articulated)	1655 kg	3648.7 lb
Tipping loads with pallet fork (straight)	1625 kg	3582.5 lb
Tipping loads with pallet fork (articulated)	1330 kg	2932.1 lb

Standard Package - WL 30

includes operator's manual and parts book

Please refer to our Price List and Ordering Guide for complete accessory information.

Specifications may change due to continuous product development. Users are advised to consult Wacker Neuson's Operator's Manual and website for specific information regarding the engine power rating. Actual power output may vary due to conditions of specific use.

Generated on Monday, August 13, 2012

